




Installation version DMK



Tendertext

Non-contact self-closing DN 15
Washtable-tap, stainless steel satin;
with rotating and lockable curved spout,
aerator*, optosensor.
For premixed water (UT mixer).
Electronically controlled - integrated
electronics (Donau/E8A, Weser/E9A).
- rotatable and lockable (Fig.) ii
Reach 220 mm
Height of outlet opening from WT 236 mm
Total height from WT 375 mm

Operating version/
EAN-Number article-number

- integrated electronic "Loex Donau", B
- external plug-in power supply unit - 12VDC

40 34154 02313 0 TG2SE8AST91ii22 5_DMK

- integrated electronic "Loex Weser", C
- external Meanwelltransformer - 12VDC

40 34154 02314 7 TG2SE8ALT91ii22 5_DMK

*Economy jet regulator up to < 6 ltr/min
a.A. against surcharge.

for Battery-operated - 6VDC

- integrated electronic "Loex Weser", E
- external batterycontainer (for 4x1,5 AA-batteries)

40 34154 02316 1 TG2SE9ABT91ii22 5_DMK



Alternatives in powder coating

Surcharge u.r., no minimum order quantity.

Signalred matt	RAL 3001
Jetblack matt	RAL 9005
Light Grey matt	RAL 7035

Shades of colour in adjacent illustrations are not binding.



Optional -

Remote control for sensor controls
in direct current (DC)

For adapting electronic parameters and activating
legionella flushing
- for Loex Donau and Loex Weser electronics -

40 34154 01393 3 Zb 073



plugadaptor for Loex Donau 12VDC
plugadaptor for Loex Weser 6VDC
IP68-connector



Meanwell-transformer for Loex Donau 12VDC
IP67; mains plug cable; IP68-connector
Velcro or screw fastening



Batterycontainer
for 4x1,5V AA-Alkalibatteries, IP68-connector
Velcro or screw fastening



DMK-Mixer-Modul-Set
solenoid-valve
Mixing by
DMK mixer for direct mounting
on angle-valve
with integrated checkvalves WC/WH
accessfilter f. angle-valve
Connecting flexhose to WH-angle-valve
angle-valve(on-site)

B

D

C

E

Tapsocket -
- rotateable and lockable (ii)
Basisdiameter 59,5 mm
Tap hole diameter 35 mm
Quick fixing for panel thicknesses up to appr. 50 mm

Supply lines-
Flexhose 3/8"cn
E8/E9 cable to source of energy
cable to solenoid-valve ca. 500 mm
ca. 600 mm
ca. 500 mm

Self-closing wash-table tap DN 15, stainless steel (AISI304L) matt
brushed; electronically controlled, with single-pipe inlet for premixed
water; with rotatable and lockable spouts, jet regulator.
Activated by the optosensor integrated into the fitting.
The electronic control systems -

tap-integrated -

- Loex Donau[E8A] (12VDC, 9 W),
- Loex Weser[E9A] (6VDC, 2 W) -

Default programm, optional remote for activating legionella flushing
and for adapting range, running times/intervals.

- Sources of energy -
- plugadaptors(12VDC resp. 6VDC)with IP68-connector
- MWTrafo 12VDC, IP67 with powercord and IP68-connector
- Batterycontainer for 4x1,5V AA-Alkalibatteries

Solenoid-valves -

- mono-stable 12VAC/DC, 2x3/8"m, Faston - for Loex Donau, Rhein
- bi-stable 6VDC, 2x3/8"m, Faston - for Loex Weser
- Flowrate ca. 19 Ltrs/min/3bar FD. Min. Flowpressure ca. 0,3bar.

Mech. Pre-mixer(brass, chrome-plated) with RüVe (WW/KW) for
direct mounting(DMK) on angle valve, connecting hose to angle valve.
Filter inserts for 3/8" angle valves enclosed.

Typ: Loex Tonga2

Also adaptable for pressure-less usage.

Also for de-mineralised water
with electronic
Loex Donau E8/24VDC and
24VDC-solenoid-valve in stainless-steel.

Subject to technical and price changes
without prior notice. This offer is subject
to change.

Our terms and conditions of sale and
delivery apply exclusively.
Status Jan 2026

Previous offers have lost their validity.
Pricing: €/p.unit; ex warehouse, packed; net.

Delivery dates on request.

Place of jurisdiction for registered tra-
ders and persons under civil law:
Frankfurt/M.

Scope of delivery: Fitting as described,
ready for installation, complete.

EU-UStID: DE111985600



LOTZ Exim Trading
Sensortechnik für Küchen-, Catering-,
Labor- und Sanitärbereiche.

Es gibt nur wenige, was sich so bezahlt macht.
- Für Sie und unsere Umwelt !